



FUEL CELLS AND HYDROGEN
JOINT UNDERTAKING

AUTORE
Automotive
deRivative Energy
system



Greg Kelsall

GE (Alstom Power UK)

www.autore-eu.com

greg.kelsall@ge.com

Programme Review Days 2018

Brussels, 14-15 November 2018

PROJECT OVERVIEW




- **Call year:** 2014
- **Call topic:** FCH-02.5-2014 – Innovative fuel cell systems at intermediate power range for distributed combined heat and power generation
- **Project dates:** 01/08/2015 – 30/04/2019
- **% stage of implementation 01/11/2018:** 87%
- **Total project budget:** 4,464,447€
- **FCH JU max. contribution:** 3,496,947€
- **Other financial contribution:** 796,850€
- **Partners:** Alstom Power Ltd (100% GE-owned), General Electric (Switzerland), Daimler AG, NuCellSyS, Helbio, University of Split, Tuscia University, SINTEF



AutoRE, Automotive deRivative Energy system

Objectives





Global positioning vs **international state-of the art**

- Apparently no commercial systems in the 50-100kWe size range

Application and market area

- combined heat and power (CHP) in commercial/industrial buildings at 50-100kWe size


Expected costs vs reciprocating engines



PARTNER ROLES



50 kW_e baseline demo in Rugby



Innovative, Lab-scale and desktop activities



- Pd-based membranes for H₂ purification: SINTEF (lead)
- Fuel cell stack operated on reformat: NucellSys+Helbio (lead)



- Modelling, diagnostic and RAMS: Univ. Split-FESB, Univ. Tuscia, GE



PROTOTYPE TEST FACILITY – layout



PROTOTYPE TEST FACILITY – in ‘real-life’



Natural gas reformer



Fuel-cell container



H2/tailgas tanks

Gas analysers and chromatograph

Natural gas storage tanks



PROJECT PROGRESS/ACTIONS – Efficiency



Achievement to-date


Electrical Efficiency of 38-40% LHV



Electrical Efficiency of 46% LHV

Initial values to be confirmed through the 50 kW 'baseline' demonstration

Aspect addressed	Parameter (KPI)	Unit	SoA 2016	FCH JU Targets		
				Call topic	2017	2020
Efficiency	Electrical efficiency	%LHV	35%-43%	46%	42-55%	42-55%
	Total efficiency	%LHV	80%	82%	NA	NA



Efficiency as a function of loading




PROJECT PROGRESS/ACTIONS – Stack life-time



Achievement to-date

Life-time 6kh
(automotive cycle)



Life-time 30kh

Aspect addressed	Parameter (KPI)	Unit	SoA 2016	FCH JU Targets		
				Call topic	2017	2020
Stack life-time	Life-time	Hours	20,000	>30,000	NA	NA

- Durability of automotive stack in stationary applications is unknown
- Experience with bus driving cycles allows for expecting >30,000 hours

Future steps:

- ‘Early’ degradation data from the 50 kW “baseline” prototype
- Utilize proprietary degradation models to estimate life-time in stationary applications





Risks and Challenges

Main bottleneck has been design/delivery of NG reformer (Task 3.1./3.3)

- Helbio initial build 6 months delayed to end of June 2017 (M23) due to upscaling task more complex than originally foreseen and sourcing of 347H steel longer than expected
- Commissioning at Helbio site revealed high reactor dP due to material choice for reformer tubes delaying delivery to Prototype test site until May 2018 (M34)
- 9 month contract extension to complete 3000h endurance test
- 3000h test started 1/10/18 but further issues with a fuel processor peripheral delayed restart to w/c 12/11/18

Additional issues due to GE acquisition of Alstom Power

- Reassignment/cancellation of project tasks eg RAMS and compact heat exchanger
- Modification of exploitation plan



Fe corrosion products blocking reactor tubes

Communications Activities



Project communication via :

Workshops/Conferences and Papers

- >25 project related publications to date (see Project website for details/links)
- AutoRE project workshop scheduled towards end of project when prototype results available

Project specific website

- <https://www.autore-eu.com/>

Local press release initiatives

- “Helbio announce delivery of H2 system for AutoRe project”
http://www.helbio.com/assets/Uploads/Press%20Release_Helbio%20AutoRE%20April%202018v.pdf
- “University of Tuscia at forefront of future of energy in Europe”
<https://www.ontuscia.it/societa/universita-della-tuscia-272106>
<https://etruriaoggi.it/universita-della-tuscia-in-prima-linea-nel-futuro-dellenergia-in-europa/>



EXPLOITATION PLAN/EXPECTED IMPACT



Exploitation

Exploitation to follow the strategy defined in Exploitation Plan

- Focus on business partners Helbio and NuCellSys/Daimler to exploit components of the system (stack and natural gas reformer)
- SINTEF has signed a license agreement with Hydrogen Mem-Tech AS in Norway for further upscaling and commercialisation of Pd-based membranes

SSERR: Support Service for the Exploitation of Research Results web-link sent to AutoRE partners

Expected Impacts

Technical impacts

- Electrical efficiency: 47%
- Thermal efficiency: >43% (90% electrical plus thermal efficiency)
- Stack life-time: >30,000 hours
- System CAPEX: <3,000 €/kW, allowing grid parity
- Scheduled/preventive maintenance to reach >98% availability, and no unforeseen shut-down for at least 2 years

Business opportunities and job creation

Improving innovation capacity

Regulations, codes and standards (RCS), and related best practice procedures

- Public domain deliverable on permitting 'lessons learned'

Benefits for the environment and European security of supply





FUEL CELLS AND HYDROGEN
JOINT UNDERTAKING

AUTORE
Automotive
deRivative Energy
system



Greg Kelsall

GE (Alstom Power UK)

www.autore-eu.com

greg.kelsall@ge.com

Programme Review Days 2018

Brussels, 14-15 November 2018