



FUEL CELLS AND HYDROGEN
JOINT UNDERTAKING


GrInHy2.0
Risk Assessment
Approach
Workshop on Safety of Electrolysis

Alexander Wooning

18 November 2020



Project Brief



Project Partner

- **Sunfire GmbH**
 - Developer and provider of the SOF steam electrolyser (HTE)
 - Responsible for manufacturing, installation, operation and maintenance
- **Paul Wurth S.A.**
 - Developer and provider of gas processing technologies
 - Responsible for the design and development of the HPU
- **Salzgitter Flachstahl GmbH**
 - Site owner and operator of the iron-and-steel works
 - Responsible for the operation and production of green hydrogen
- **Salzgitter Mannesmann Forschung GmbH**
 - Centralized research and development (R&D)
 - Responsible for the overall project coordination and the full Life Cycle Assessment




Project Partner

- **Tenova S.a.P.**
 - Developer of innovative technologies and services for the metal and mining industries
 - Creates a study on the CO₂ avoidance potential of hydrogen in the European steel industry
- **CEA - Commissariat à l'énergie atomique et aux énergies alternatives**
 - Key player in research, development and innovation
 - Provides long term stack tests as well as an energy management strategy assessment



Project Objectives

- **Technical:**
 - Electrolyser scale-up to 720 kW_{el,AC} producing 200 Nm³/h (18 kg/h)
 - Electrical electrolyser efficiency up to 84 %_{LHV}
 - >13,000 operating hours at system level with a proved availability of >95 %
 - > 20,000 operating hours at stack level
- **Economical:**
 - Produce >100 tons of green hydrogen at under 7 €/kgH₂
 - Reduce electrolyser CAPEX to <4,500 €/(kgH₂/d)
- **Socio-political:**
 - Create viable technology by demonstration in a complex industrial environment
 - Assess CO₂ avoidance potential of a hydrogen-based European steel industry
 - Provide significant share of green hydrogen to the iron-and-steel works



Regulations, Codes and Standards

Directives:

- Directive 2014/35/EU - Low Voltage Directive
(Full conformity assessment)
- Directive 2014/68/EU – Pressure Equipment Directive
- Directive 2014/30/EU - Electromagnetic Compatibility Directive
- Directive 2011/65/EU - RoHS Directive

Codes & Standards:

- DIN EN ISO 12100:2011-03; Safety of machinery - General principles for design - Risk assessment and risk reduction
- DIN EN ISO 13849-1:2016-06; Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design
- DIN EN 60204-1:2019-06; Safety of machinery - Electrical equipment of machines - Part 1: General requirements
- DIN EN IEC 61000-6-2:2019-11; Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity standard for industrial environments
- DIN EN 61000-6-3:2011-09; Electromagnetic compatibility (EMC) - Part 6-3: Generic standards - Emission standard for residential, commercial and light-industrial environments
- DIN EN 61511-1:2019-02; Functional safety - Safety instrumented systems for the process industry sector
- ISO 22734:2019-09; Hydrogen generators using water electrolysis - Industrial, commercial, and residential applications

Risk Assessments – System Level

- **Phase 1: Risk Assessment Basis – ISO 22734**
 - ISO 22734:2019-09 - Hydrogen generators using water electrolysis - Industrial, commercial, and residential applications
 - Covers general design rules for electrolyser to cover general risks and hazards
- **Phase 2: Individual project specific Risk Assessment**
 - Identifying risks that are not a result of abnormal operational conditions during all life phases
- **Phase 3: HAZOP**
 - Identifying and assessing risks induced by abnormal operational occurrences during all operational states



Prevention and mitigation – ATEX hazard mitigation

Normal Operation:

- Hydrogen containing pipes are technically tight
- Ambient pressure operation results in very small potential leakage rates
- Gas-space around the stacks is equipped with a temperature safeguard, which prevents entering burnable gases below the ignition temperature
- Gas sensors are used as additional safeguards
- All pipes and sensors are inspected and maintained on a regular basis

Postulated Worst Case Incident: Cracked welding of H₂ containing pipe

- **Design and Construction:** Full enclosure of the electrolyser with forced ventilation
Exhaust of gases via roof result in ATEX Zone 2
Ensure no ignition sources on top of electrolyser
- **Protective Measures:** If gas sensors detect high elevated concentration shut down is immediately initiated
- **Information /Organizational countermeasures:** No personnel allowed on top of electrolyser during operation
Warning signs, operational instruction, and training of personnel

Copyrights

This presentation is subject to statutory copyright law. All rights to images included in this presentation are owned by Sunfire GmbH or the respective GrInHy2.0 project partners. All rights reserved.

Trademarks

Sunfire and the Droplet/Flame logo are registered trademarks of Sunfire GmbH. Other company names, product names and logos may be registered trademarks of the GrInHy2.0 project partners. The simple mention of trademarked elements without marking within this presentation does not indicate that they are not protected by registered trademarks.



FUEL CELLS AND HYDROGEN
JOINT UNDERTAKING

Alexander Wooning

Safety Engineer
Alexander.Wooning@sunfire.de

For further information

www.fch.europa.eu



@fch_ju



Fch-ju@fch.europa.eu



FCH JU